




	SOLERA T	SOLERA S	SOLERA L
			
Outer Lite	Glass	Glass	Glass
Inner Lite	Glass	Glass	Glass
Annealed	Available	Available	Available
Tempered	Available	Available	Available
Laminated	Available	Available	Available
Tinted	Available	Available	Available
Low e	Not Necessary	Not Necessary	Not Necessary
Module	None	None	None
Internal Mullions	None	None	None
Size Limits	1524mmX3658mm 60"X144"	1524mmX3658mm 60"X144"	1524mmX3658mm 60"X144"
Framing system	Any curtain wall system greater than 4" deep (minimum mullion depth of 2")	Any window system greater than 4" deep plus storefront systems with pressure bars	Any system that accommodates a nominal 1" IGU
Operable windows	Not Applicable	Not Applicable	Applicable
Visible Light Transmittance	3% > 73%	3% > 73%	3% > 67%
Shading coefficient	.04>.75	.04>.75	.04>.75
Light Diffusing Power	Excellent	Excellent	Moderate to Excellent
U value	0.20 BTU/s.f./h.r°F	0.20 BTU/s.f./h.r°F	0.45 BTU/s.f./h.r°F
STC	44 and up	44 and up	35

* Minimum mullion depth 3" for overhead applications